

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

1 Identification of the substance/preparation and of the company/undertaking

Product details

Trade name **Deitermann KM Flex (weiß)**

Safety data sheet no.: 49PD10304/5

Application of the substance / the preparation Tile adhesive

Manufacturer/Supplier:

maxit France s.a.s
4 rue de Mulhouse
Boîte Postale 27
F-68180 Horbourg-Wihr
Tel.: ++33(0)3 89 20 10 80
FAX: ++33(0)3 89 20 10 92

Information in case of emergency:

maxit France s.a.s
Tel.: ++33(0)3 89 20 10 80

2 Composition/information on ingredients

Chemical characterization

Description: Ready-mixed mortar with Portland cement

Dangerous components:

65997-15-1	cement, portland, white	 Xi; R 38-41	25 - 50%
14808-60-7	Siliciumdioxide (Quartzsand)		25 - 50%
1317-65-3	limestone		5 - 10%

Additional information For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

Hazard description:



Xi Irritant

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 38 Irritating to skin.

R 41 Risk of serious damage to eyes.

Product has a strong alkaline reaction with water; therefore protect skin and eyes from corrosive properties.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First aid measures

General information Immediately remove any clothing soiled by the product.

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 2)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Deitermann KM Flex (weiß)

(Contd. of page 1)

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

Information for doctor None

5 Fire fighting measures

Suitable extinguishing agents

Use fire extinguishing methods suitable to surrounding conditions.

Protective equipment: Use methods suitable to surrounding conditions.

6 Accidental release measures

Person-related safety precautions:

Wear protective clothing.

Avoid formation of dust.

Ensure adequate ventilation.

Measures for environmental protection:

Do not allow product to reach sewage system or any water course.

Measures for cleaning/collecting:

Pick up mechanically.

Dispose of the material collected according to regulations.

Additional information: See Section 13 for disposal information.

7 Handling and storage

Handling

Information for safe handling:

Prevent formation of dust.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility:

Do not store together with acids.

Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water.

8 Exposure controls and personal protection

Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Deitermann KM Flex (weiß)

(Contd. of page 2)

Ingredients with limit values that require monitoring at the workplace:

Additional information:

Te applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter P2.

Protection of hands:

Protective gloves.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Nitrile impregnated cotton gloves.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles

Body protection: Protective work clothing.

9 Physical and chemical properties:

General Information

Form:	Powder
Colour:	White
Odour:	Characteristic

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

Flash point: Not applicable

Flammability (solid, gaseous): Product is not flammable.

Self-igniting: Product is not selfigniting.

(Contd. on page 4)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Deitermann KM Flex (weiß)

(Contd. of page 3)

Danger of explosion:	Product does not present an explosion hazard.
Vapour pressure:	Not applicable.
Density:	Not applicable.
Bulk density:	1400 kg/m ³
Solubility in / Miscibility with Water at 20°C (68°F):	1,5 g/l
pH-value at 20°C (68°F):	>12,0 (DIN 19261) In water
Viscosity:	
dynamic:	Not applicable.
kinematic:	Not applicable.
Solvent content:	
Organic solvents:	0,0 %
Solids content:	100,0 %
Additional information:	None.

10 Stability and reactivity

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

Dangerous reactions:

Reacts with acids

Reacts with light alloys in the presence of moisture to form hydrogen

Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Acute toxicity:

LD/LC50 values relevant for classification:

Components	Type	Value	Species
1317-65-3 limestone			
Oral	LD50	> 5000 mg/kg	(rat)

Primary irritant effect:

on the skin: Irritant to skin and mucous membranes.

on the eye: Strong irritant with the danger of severe eye injury.

Sensitization: No sensitizing effects known.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information:

Information about elimination (persistence and degradability):

Other information: The product is difficultly biodegradable.

(Contd. on page 5)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Deitermann KM Flex (weiß)

(Contd. of page 4)

Ecotoxical effects:

Remark:

The product contains substances which causes severe clouding in water

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Remark: The product causes a significant pH change. Neutralise before introduction.

General notes:

Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

Product:

Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish.

European waste catalogue

10 13 11	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10
10 13 14	waste concrete and concrete sludge

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Recommended cleaning agent:

Water, if necessary together with cleansing agents.

Thoroughly shake out sacks.

14 Transport information

Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)

ADR/RID-GGVS/E Class: -

Maritime transport IMDG/GGVSea:

IMDG/GGVSea Class: -

Air transport ICAO-TI and IATA-DGR:

ICAO/IATA Class: -

Transport/Additional information: Not dangerous according to the above specifications.

15 Regulatory information

Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Observe the general safety regulations when handling chemicals.

(Contd. on page 6)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Deitermann KM Flex (weiß)

(Contd. of page 5)

Code letter and hazard designation of product:



Xi Irritant

Hazard-determining components of labelling:

cement, portland, white

Risk phrases:

38 Irritating to skin.

41 Risk of serious damage to eyes.

Safety phrases:

2 Keep out of the reach of children.

22 Do not breathe dust.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

28 After contact with skin, wash immediately with plenty of water.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

46 If swallowed, seek medical advice immediately and show this container or label.

Special labelling of certain preparations:

Product has a strong alkaline reaction with water; therefore protect skin and eyes from corrosive properties.

16 Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant R-phrases

38 Irritating to skin.

41 Risk of serious damage to eyes.

Department issuing MSDS: Product safety department

Contact: Mr Gilles Weber, Tel.: ++33(0)3 89 20 10 93

* Data compared to the previous version altered.