

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

1 Identification of the substance/preparation and of the company/undertaking**Product details**Trade name **Eurolan 1**

Safety data sheet no.: 49PD10338/7

Application of the substance / the preparation Bitumen coating

Manufacturer/Supplier:

maxit France s.a.s
 4 rue de Mulhouse
 Boîte Postale 27
 F-68180 Horbourg-Wihr
 Tel.: ++33(0)3 89 20 10 80
 FAX: ++33(0)3 89 20 10 92

Information in case of emergency:

maxit France s.a.s
 Tel.: ++33(0)3 89 20 10 80

2 Composition/information on ingredients**Chemical characterization****Description:** Preparation on the base of bitumen, solvents and ancillary substances**Dangerous components:**

8052-42-4	Asphalt	> 50%
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy  Xn,  N; R 10-51/53-65-66-67	25 - 50%

Additional information For the wording of the listed risk phrases refer to section 16.**3 Hazards identification****Hazard description:**

N Dangerous for the environment

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

R 10 Flammable.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

EU

(Contd. on page 2)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan 1

(Contd. of page 1)

4 First aid measures

General information

Immediately remove any clothing soiled by the product.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

Information for doctor

Treatment

If swallowed or in case of vomiting, danger of entering the lungs

Later observation for pneumonia and pulmonary oedema.

5 Fire fighting measures

Suitable extinguishing agents

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents Water with full jet

Special hazards caused by the substance, its products of combustion or resulting gases:

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Carbon monoxide (CO)

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

Person-related safety precautions:

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

Ensure adequate ventilation.

Measures for environmental protection:

Inform respective authorities in case of seepage into water course or sewage system.

The product must not get into watercourses or into the soil.

Suppress gases/fumes/haze with water spray.

Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan 1**Additional information:** See Section 13 for disposal information.

(Contd. of page 2)

7 Handling and storage**Handling****Information for safe handling:**

Keep away from heat and direct sunlight.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

Storage**Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

Store in a cool location.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Recommended storage temperature: 5-30°C.**8 Exposure controls and personal protection****Additional information about design of technical facilities:** No further data; see item 7.**Ingredients with limit values that require monitoring at the workplace:****Additional information:**

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

Personal protective equipment:**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and feed.

Do not eat, drink, smoke or sniff while working.

Wash hands before breaks and at the end of work.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory

filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter AX.

Protection of hands:

Solvent resistant gloves

(Contd. on page 4)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan 1

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles**Body protection:** Protective work clothing.**9 Physical and chemical properties:****General Information**

Form:	Fluid
Colour:	Black
Odour:	Characteristic

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	> 132°C (> 270°F) (DIN)

Flash point:	25°C (77°F) (DIN ISO 2592)
---------------------	----------------------------

Ignition temperature:	ca.240°C (ca.464°F)
------------------------------	---------------------

Self-igniting:	Product is not selfigniting.
-----------------------	------------------------------

Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
-----------------------------	---

Explosion limits:

Lower:	0,7 Vol %
Upper:	6,5 Vol %

Vapour pressure at 20°C (68°F):	8 hPa (6 mm Hg)
--	-----------------

Density at 20°C (68°F):	0,91 g/cm ³ (DIN 51757)
--------------------------------	------------------------------------

Bulk density:	Not applicable.
----------------------	-----------------

Solubility in / Miscibility with

Water:	Unsoluble
---------------	-----------

pH-value:	Not applicable.
------------------	-----------------

Viscosity:

dynamic at 20°C (68°F):	ca.500 mPas (DIN 53019)
kinematic at 40°C (104°F):	>7,0 mm ² /s (DIN ISO 2431)

Solvent content:

Organic solvents:	38,0 %
--------------------------	--------

Additional information:	None.
--------------------------------	-------

EU

(Contd. on page 5)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan 1

(Contd. of page 4)

10 Stability and reactivity**Thermal decomposition / Conditions to be avoided:**

No decomposition if used according to specifications.

Dangerous reactions: Reacts with strong oxidizing agents**Dangerous decomposition products:**

Carbon monoxide

Hydrogen sulphide

Hydrocarbons

11 Toxicological information**Acute toxicity:****LD/LC50 values relevant for classification:**

Components	Type	Value	Species
64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy			
Oral	LD50	>2000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rat)	
Inhalative	LC50/4 h	>5 mg/l (rat)	

Primary irritant effect:**on the skin:** Skin irritation possible due to drying effect.**on the eye:** Slightly irritating**Sensitization:** No sensitizing effects known.**Additional toxicological information:**

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

12 Ecological information:**Information about elimination (persistence and degradability):****Other information:** The product is difficultly biodegradable.**Ecotoxicological effects:****Remark:**

The product contains substances which causes severe clouding in water

The product contains substances which are toxic to fishes and bacteria.

General notes:

Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations**Product:****Recommendation**

After prior treatment product has to be landfilled or incinerated adhering to the regulations pertaining to the disposal of especially hazardous waste.

European waste catalogue

17 03 02 bituminous mixtures other than those mentioned in 17 03 01

(Contd. on page 6)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan 1

(Contd. of page 5)

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

14 Transport information

Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)

ADR/RID-GGVS/E Class: -

Maritime transport IMDG/GGVSea:

IMDG/GGVSea Class: -

Air transport ICAO-TI and IATA-DGR:



ICAO/IATA Class: 3

UN/ID Number: 1999

Label 3

Packaging group: III

Proper shipping name: TARS, LIQUID

15 Regulatory information

Labelling according to EU guidelines:

The product has been marked in accordance with EU Directives / respective national laws.

Observe the general safety regulations when handling chemicals.

Code letter and hazard designation of product:



N Dangerous for the environment

Risk phrases:

10 Flammable.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

Safety phrases:

2 Keep out of the reach of children.

16 Keep away from sources of ignition - No smoking.

23 Do not breathe fumes.

24/25 Avoid contact with skin and eyes.

60 This material and its container must be disposed of as hazardous waste.

61 Avoid release to the environment. Refer to special instructions/safety data sheets.

EU

(Contd. on page 7)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan 1

(Contd. of page 6)

16 Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant R-phrases

10 Flammable.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

Department issuing MSDS: Product safety department**Contact:** Mr Gilles Weber, Tel.: ++33(0)3 89 20 10 93*** Data compared to the previous version altered.**

EU