

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

1 Identification of the substance/preparation and of the company/undertaking**Product details**Trade name **Eurolan FK 43 Komp. A**

Safety data sheet no.: 49PD10363-a/4

Application of the substance / the preparation Epoxy coating

Manufacturer/Supplier:

maxit France s.a.s

4 rue de Mulhouse

Boîte Postale 27

F-68180 Horbourg-Wihr

Tel.: ++33(0)3 89 20 10 80

FAX: ++33(0)3 89 20 10 92

Information in case of emergency:

maxit France s.a.s

Tel.: ++33(0)3 89 20 10 80

2 Composition/information on ingredients**Chemical characterization****Description:** Reaction resin based on bisphenol-A and F**Dangerous components:**

25085-99-8	Bisphenoel-A-Epichlorhydrine-Resin MG < 700  Xi,  N; R 36/38-43-51/53	5 - 10%
28064-14-4	Bisphenole-F-Epichlorhydrine-Resin MG ≤ 700  Xi,  N; R 36/38-43-51/53	2 - 5%
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs  Xi,  N; R 36/38-43-51/53	1 - 2%
34590-94-8	(2-methoxymethylethoxy)propanol	1 - 2%

Additional information For the wording of the listed risk phrases refer to section 16.**3 Hazards identification****Hazard description:**

Xi Irritant

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 43 May cause sensitisation by skin contact.

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Contains epoxy constituents. See information supplied by the manufacturer.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

EU

(Contd. on page 2)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK 43 Komp. A

(Contd. of page 1)

4 First aid measures

General information

Immediately remove any clothing soiled by the product.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Rinse liquid should be tempered (20-30°C).

After swallowing Drink plenty of water and provide fresh air. Call for a doctor immediately.

Information for doctor None

5 Fire fighting measures

Suitable extinguishing agents

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents Water with full jet

Protective equipment: Wear self-contained respiratory protective device.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

Person-related safety precautions:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Measures for environmental protection:

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

The product must not get into watercourses

or into the soil.

Suppress gases/fumes/haze with water spray.

Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Additional information: See Section 13 for disposal information.

7 Handling and storage

Handling

Information for safe handling: Store in cool, dry place in tightly closed receptacles.

Information about fire - and explosion protection: No special measures required.

Storage

Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK 43 Komp. A

(Contd. of page 2)

Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with acids.

Store away from oxidizing agents.

Store away from reducing agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from frost.

Protect from heat and direct sunlight.

8 Exposure controls and personal protection**Additional information about design of technical facilities:** No further data; see item 7.**Ingredients with limit values that require monitoring at the workplace:**

CAS No.	Designation of material	%	Type	Value	Unit
34590-94-8 (2-methoxymethylethoxy)propanol					
IOELV ()	308 mg/m ³ , 50 ppm				
	Skin				

Additional information:

Te applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

Personal protective equipment:**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Use a moisturising skin cream after processing the product.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter AX.

Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK 43 Komp. A

(Contd. of page 3)

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles

Body protection: Impervious protective clothing

9 Physical and chemical properties:**General Information**

Form:	Fluid
Colour:	According to product specification
Odour:	Weak, characteristic

Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 100°C (212°F) (DIN)

Flash point: 252°C (486°F) (DIN ISO 2592)

Self-igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Density at 20°C (68°F): 1,79 g/cm³ (DIN 51757)

Bulk density: Not applicable.

Solubility in / Miscibility with

Water: Fully miscible

pH-value: Not applicable.

Viscosity:

dynamic: Not determined.
kinematic: Not determined.

Solvent separation test: Not applicable.

Solvent content:

Organic solvents: 0 %

Additional information: None.

10 Stability and reactivity**Thermal decomposition / Conditions to be avoided:**

To avoid thermal decomposition do not overheat.

Dangerous reactions:

Contact with aliphatic amines results in an irreversible polymerisation with considerable thermic development.

Reacts with acids, alkalis and oxidizing agents

Dangerous decomposition products: No dangerous decomposition products known.

EU

(Contd. on page 5)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK 43 Komp. A

(Contd. of page 4)

11 Toxicological information**Acute toxicity:**

LD/LC50 values relevant for classification:

Components		Type	Value	Species
25085-99-8 Bisphenoel-A-Epichlorhydrine-Resin MG < 700				
Oral	LD50	> 5000 mg/kg (rat)		
Dermal	LD50	> 2000 mg/kg (rabbit)		
28064-14-4 Bisphenole-F-Epichlorhydrine-Resin MG ≤ 700				
Oral	LD50	23800 mg/kg (rat)		
Dermal	LD50	> 2000 mg/kg (rabbit)		

Primary irritant effect:**on the skin:** Irritant to skin and mucous membranes.**on the eye:** Irritating effect.**Sensitization:** Sensitization possible through skin contact.**Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information:**Information about elimination (persistence and degradability):****Other information:** The product is difficultly biodegradable.**Ecotoxicological effects:****Remark:** Harmful to fish**General notes:**

Do not allow product to reach ground water, water course or sewage system.

Harmful to aquatic organisms

Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations**Product:****Recommendation**

Curing of the product by mixing with the curing component. Cured epoxy resin products are waste that requires no particular supervision and can as a rule be disposed of as commercial waste that is similar to household rubbish.

European waste catalogue

07 02 08 | other still bottoms and reaction residues

Uncleaned packaging:**Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Disposal must be made according to official regulations.

Recommended cleaning agent: Water, if necessary together with cleansing agents.

EU

(Contd. on page 6)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK 43 Komp. A

(Contd. of page 5)

14 Transport information**Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)**
ADR/RID-GGVS/E Class: -**Maritime transport IMDG/GGVSea:**

IMDG/GGVSea Class: -

Marine pollutant: No

Air transport ICAO-TI and IATA-DGR:

ICAO/IATA Class: -

Transport/Additional information: Not dangerous according to the above specifications.**15 Regulatory information****Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Observe the general safety regulations when handling chemicals.

Code letter and hazard designation of product:

Xi Irritant

Hazard-determining components of labelling:

Bisphenoel-A-Epichlorhydrine-Resin MG < 700

Bisphenole-F-Epichlorhydrine-Resin MG ≤ 700

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Risk phrases:

43 May cause sensitisation by skin contact.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

2 Keep out of the reach of children.

23 Do not breathe fumes.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

28 After contact with skin, wash immediately with plenty of water.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

46 If swallowed, seek medical advice immediately and show this container or label.

Special labelling of certain preparations:

Contains epoxy constituents. See information supplied by the manufacturer.

16 Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant R-phrases

36/38 Irritating to eyes and skin.

43 May cause sensitisation by skin contact.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 7)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK 43 Komp. A

(Contd. of page 6)

Department issuing MSDS: Product safety department**Contact:** Mr Gilles Weber, Tel.: ++33(0)3 89 20 10 93*** Data compared to the previous version altered.**

EU

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

1 Identification of the substance/preparation and of the company/undertaking**Product details**Trade name **Eurolan FK 43 Komp.B**

Safety data sheet no.: 49PD10363-b/4

Application of the substance / the preparation Construction chemicals

Manufacturer/Supplier:

maxit France s.a.s
 4 rue de Mulhouse
 Boîte Postale 27
 F-68180 Horbourg-Wihr
 Tel.: ++33(0)3 89 20 10 80
 FAX: ++33(0)3 89 20 10 92

Information in case of emergency:

maxit France s.a.s
 Tel.: ++33(0)3 89 20 10 80

2 Composition/information on ingredients**Chemical characterization**

Description: Modified aminic hardeners.

Dangerous components:

	Polyamin - Epoxy Harzstoffaddukte  Xi; R 41	25 - 50%
	Polyamin-Epoxidharzaddukt  Xn,  Xi; R 22-41	5 - 10%
9046-10-0	POLYOXYPROPYLENE DIAMINE  C,  Xn; R 21/22-34-52/53	2 - 5%
93941-62-9	3-[(6-aminotrimethylhexyl)amino]propiononitrile  C,  Xn; R 22-34-43	2 - 5%
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine  C,  Xn; R 21/22-34-43-52/53	1 - 2%

Additional information For the wording of the listed risk phrases refer to section 16.

3 Hazards identification**Hazard description:**

C Corrosive

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 34 Causes burns.

R 43 May cause sensitisation by skin contact.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

EU

(Contd. on page 2)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK 43 Komp.B

(Contd. of page 1)

4 First aid measures**General information**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation Supply fresh air and to be sure call for a doctor.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

Call a doctor immediately.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing Drink plenty of water and provide fresh air. Call for a doctor immediately.

Information for doctor

Treatment If swallowed, gastric irrigation with added, activated carbon.

5 Fire fighting measures**Suitable extinguishing agents**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards caused by the substance, its products of combustion or resulting gases:

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NO_x)

Protective equipment: Wear self-contained respiratory protective device.

6 Accidental release measures**Person-related safety precautions:**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Measures for environmental protection:

The product must not get into watercourses or into the soil.

Suppress gases/fumes/haze with water spray.

Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Additional information: See Section 13 for disposal information.

7 Handling and storage**Handling****Information for safe handling:**

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection: No special measures required.

Storage**Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK 43 Komp.B

(Contd. of page 2)

Information about storage in one common storage facility: Store away from foodstuffs.**Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Protect from frost.

Protect from heat and direct sunlight.

Recommended storage temperature: 5-30°C.**8 Exposure controls and personal protection****Additional information about design of technical facilities:** No further data; see item 7.**Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information:

Te applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

Personal protective equipment:**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter AX.

Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles**Body protection:** Protective work clothing.

EU

(Contd. on page 4)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK 43 Komp.B

(Contd. of page 3)

9 Physical and chemical properties:**General Information**

Form:	Fluid
Colour:	According to product specification
Odour:	Amine-like

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100°C (212°F) (DIN)

Flash point:	> 100°C (> 212°F) (DIN ISO 2592)
---------------------	----------------------------------

Self-igniting:	Product is not selfigniting.
-----------------------	------------------------------

Danger of explosion:	Product does not present an explosion hazard.
-----------------------------	---

Vapour pressure at 20°C (68°F):	23 hPa (17 mm Hg) (DIN 51640)
--	-------------------------------

Density at 20°C (68°F):	1,08 g/cm ³ (DIN 51757)
--------------------------------	------------------------------------

Bulk density:	Not applicable.
----------------------	-----------------

Solubility in / Miscibility with

Water:	miscible
---------------	----------

pH-value at 20°C (68°F):	ca.9,2 (DIN 19261)
---------------------------------	--------------------

Viscosity:

dynamic:	Not determined.
kinematic:	Not determined.

Solvent separation test:	Not determined
---------------------------------	----------------

Solvent content:

Organic solvents:	0,0 %
--------------------------	-------

Additional information:	None.
--------------------------------	-------

10 Stability and reactivity**Thermal decomposition / Conditions to be avoided:**

No decomposition if used according to specifications.

Dangerous reactions:

Reacts with peroxides

Reacts with strong oxidizing agents

Dangerous decomposition products:

Carbon monoxide and carbon dioxide

Ammonia

Nitrogen oxides (NO_x)**11 Toxicological information****Acute toxicity:****LD/LC50 values relevant for classification:**

Components	Type	Value	Species
Polyamin-Epoxidharzaddukt			
Oral	LD50	788 mg/kg	(rat)
9046-10-0 POLYOXYPROPYLENE DIAMINE			
Oral	LD50	2855 mg/kg	(rat)
Dermal	LD50	2140 mg/kg	(rabbit)

(Contd. on page 5)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK 43 Komp.B

(Contd. of page 4)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral	LD50	1030 mg/kg (rat)
Dermal	LD50	1840 mg/kg (rabbit)

Primary irritant effect:**on the skin:** Caustic effect on skin and mucous membranes.**on the eye:** Strong caustic effect.**Sensitization:** Sensitization possible through skin contact.**Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Harmful

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

12 Ecological information:**Information about elimination (persistence and degradability):****Other information:** The product is difficultly biodegradable.**Behaviour in environmental systems:****Mobility and bioaccumulation potential:****2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

EBAB	0,79 log Pow (-)
------	------------------

Ecotoxicological effects:**Aquatic toxicity:****Type of test Effective concentration Method Assessment****9046-10-0 POLYOXYPROPYLENE DIAMINE**

EC50/72h	135 mg/l (scenedesmus subspicatus (Alge))
LC50/48h	48 mg/l (Daphnia magna (großer Wasserfloh))
LC50/96h	> 100 mg/l (Oncorhynchus mykiss (rainbow trout))

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

EC 10/18h	1120 mg/l (pseudomonas putida)
EC50/24h	42 mg/l (Daphnia magna (großer Wasserfloh))
EC50/72h	37 mg/l (scenedesmus subspicatus (Alge))
LC50/48h	185 mg/l (Leuciscus idus (Goldorfe))
LC50/96h	110 mg/l (Brachydanio rerio (Zebrafisch))

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Remark: The product causes a significant pH change. Neutralise before introduction.**General notes:**

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

EU

(Contd. on page 6)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK 43 Komp.B

(Contd. of page 5)

13 Disposal considerations

Product:

Recommendation

After mixing with the resin component pour a partial amount back into the curing agent barrel, stir well and pour the mass back once more. Cured epoxy resin products are waste that requires no particular supervision and can as a rule be disposed of as commercial waste that is similar to household rubbish.

European waste catalogue

07 02 08 other still bottoms and reaction residues

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Recommended cleaning agent: Water, if necessary together with cleansing agents.

14 Transport information

Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)



ADR/RID-GGVS/E Class: 8 (C7) Corrosive substances.

Danger code (Kemler): 80

UN-Number: 2735

Packaging group: III

Hazard label 8

Description of goods: 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (POLYOXYPROPYLENE DIAMINE, 3-[(6-aminotrimethylhexyl)amino]propiononitrile)

Maritime transport IMDG/GGVSea:



IMDG/GGVSea Class: 8

UN Number: 2735

Label 8

Packaging group: III

EMS Number: F-A,S-B

Marine pollutant: No

Proper shipping name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (POLYOXYPROPYLENE DIAMINE, 3-[(6-aminotrimethylhexyl)amino]propiononitrile)

Air transport ICAO-TI and IATA-DGR:



ICAO/IATA Class: 8

UN/ID Number: 2735

(Contd. on page 7)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK 43 Komp.B

(Contd. of page 6)

Label	8
Packaging group:	III
Proper shipping name:	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (POLYOXYPROPYLENE DIAMINE, 3-[(6-aminotrimethylhexyl)amino] propiononitrile)

15 Regulatory information**Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
Observe the general safety regulations when handling chemicals.

Code letter and hazard designation of product:

C Corrosive

Hazard-determining components of labelling:

3-[(6-aminotrimethylhexyl)amino]propiononitrile
3-aminomethyl-3,5,5-trimethylcyclohexylamine

Risk phrases:

34 Causes burns.
43 May cause sensitisation by skin contact.

Safety phrases:

2 Keep out of the reach of children.
23 Do not breathe fumes.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
28 After contact with skin, wash immediately with plenty of water.
36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
46 If swallowed, seek medical advice immediately and show this container or label.

16 Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant R-phrases

21/22 Harmful in contact with skin and if swallowed.
22 Harmful if swallowed.
34 Causes burns.
41 Risk of serious damage to eyes.
43 May cause sensitisation by skin contact.
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Department issuing MSDS: Product safety department

Contact: Mr Gilles Weber, Tel.: ++33(0)3 89 20 10 93

* Data compared to the previous version altered.