

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

1 Identification of the substance/preparation and of the company/undertaking**Product details**Trade name **Eurolan FK Inject Komp.A**

Safety data sheet no.: 49PD10578-a/7

Application of the substance / the preparation Epoxy sealing

Manufacturer/Supplier:

maxit France s.a.s
 4 rue de Mulhouse
 Boîte Postale 27
 F-68180 Horbourg-Wihr
 Tel.: ++33(0)3 89 20 10 80
 FAX: ++33(0)3 89 20 10 92

Information in case of emergency:

maxit France s.a.s
 Tel.: ++33(0)3 89 20 10 80

2 Composition/information on ingredients**Chemical characterization****Description:** Reaction resin based on bisphenol-A and F**Dangerous components:**

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)  Xi,  N; R 36/38-43-51/53	25 - 50%
28064-14-4	Bisphenole-F-Epichlorhydrine-Resin MG ≤ 700  Xi,  N; R 36/38-43-51/53	10 - 25%
68081-84-5	C13/C15 - Alkylglycidylether  Xi,  N; R 36/38-43-51/53	5 - 10%

Additional information For the wording of the listed risk phrases refer to section 16.**3 Hazards identification****Hazard description:**

Xi Irritant
 N Dangerous for the environment

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 36/38 Irritating to eyes and skin.

R 43 May cause sensitisation by skin contact.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Contains epoxy constituents. See information supplied by the manufacturer.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

EU

(Contd. on page 2)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK Inject Komp.A

(Contd. of page 1)

4 First aid measures**General information**

Immediately remove any clothing soiled by the product.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation Supply fresh air and to be sure call for a doctor.**After skin contact**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing Drink plenty of water and provide fresh air. Call for a doctor immediately.**Information for doctor** None**5 Fire fighting measures****Suitable extinguishing agents**CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**For safety reasons unsuitable extinguishing agents** Water with full jet**Special hazards caused by the substance, its products of combustion or resulting gases:**

During heating or in case of fire poisonous gases are produced.

Protective equipment: Wear self-contained respiratory protective device.**Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures**Person-related safety precautions:**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Measures for environmental protection:

Inform respective authorities in case of seepage into water course or sewage system.

The product must not get into watercourses or into the soil.

Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

7 Handling and storage**Handling****Information for safe handling:**

Store in cool, dry place in tightly closed receptacles.

Use only in well ventilated areas.

Information about fire - and explosion protection: No special measures required.

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK Inject Komp.A

(Contd. of page 2)

Storage**Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

Store in a cool location.

Information about storage in one common storage facility:

Store away from reducing agents.

Store away from oxidizing agents.

Do not store together with alkalis (caustic solutions).

Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from frost.

Protect from heat and direct sunlight.

Recommended storage temperature: 5-30°C.**8 Exposure controls and personal protection****Additional information about design of technical facilities:** No further data; see item 7.**Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information:

Te applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

Personal protective equipment:**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Do not eat, drink, smoke or sniff while working.

Respiratory protection:

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter AX.

Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK Inject Komp.A

(Contd. of page 3)

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles

Body protection: Protective work clothing.

9 Physical and chemical properties:**General Information**

Form:	Fluid
Colour:	Transparent
Odour:	Weak, characteristic

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: > 200°C (> 392°F) (DIN)

Flash point: > 100°C (> 212°F) (DIN ISO 2592)

Ignition temperature: >300°C (>572°F) (DIN 51794)

Self-igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Density at 20°C (68°F): 0,83 g/cm³ (DIN 51757)

Bulk density: Not applicable.

Solubility in / Miscibility with

Water: Insoluble

pH-value: Not applicable.

Viscosity:

dynamic: Not determined.

kinematic: Not determined.

Solvent separation test: Not determined

Solvent content:

Organic solvents: 0,0 %

Additional information: None.

10 Stability and reactivity**Thermal decomposition / Conditions to be avoided:**

No decomposition if used according to specifications.

To avoid thermal decomposition do not overheat.

Dangerous reactions: Reacts with acids, alkalis and oxidizing agents

Dangerous decomposition products: No dangerous decomposition products known.

EU

(Contd. on page 5)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK Inject Komp.A

(Contd. of page 4)

11 Toxicological information**Acute toxicity:**

LD/LC50 values relevant for classification:

Components	Type	Value	Species
25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)			
Oral	LD50	11400 mg/kg (rat)	
Dermal	LD50	> 2000 mg/kg (rabbit)	
26142-30-3 Polypropylenglykol-Diepoxidharz			
Oral	LD50	> 4000 mg/kg (rat)	
Dermal	LD50	> 2000 mg/kg (rat)	
28064-14-4 Bisphenole-F-Epichlorhydrine-Resin MG ≤ 700			
Oral	LD50	23800 mg/kg (rat)	
Dermal	LD50	> 2000 mg/kg (rabbit)	
68081-84-5 C13/C15 - Alkylglycidylether			
Oral	LD50	> 5000 mg/kg (rat)	

Primary irritant effect:**on the skin:** Irritant to skin and mucous membranes.**on the eye:** Irritating effect.**Sensitization:** Sensitization possible through skin contact.**Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information:**Information about elimination (persistence and degradability):****Other information:** The product is difficultly biodegradable.**Behaviour in environmental systems:****Mobility and bioaccumulation potential:**

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)	
Bioakkumulation	3,5 - 4 log Pow (-)

Ecotoxicological effects:**Acquatic toxicity:**

Type of test	Effective concentration	Method	Assessment
25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)			
EC50/24h	1,1 - 3,6 mg/l	(Daphnia magna (großer Wasserfloh))	
EC50/96h	220 mg/l	(Selenastrum capricornutum (Grünalge))	
LC50/96h	1,5 - 7,7 mg/l	(Oncorhynchus mykiss (rainbow trout))	

Remark:

The product contains substances which causes severe clouding in water

The product contains substances which are toxic to fishes and bacteria.

General notes:

Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 6)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK Inject Komp.A

(Contd. of page 5)

Toxic for aquatic organisms
 Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations**Product:****Recommendation**

Curing of the product by mixing with the curing component. Cured epoxy resin products are waste that requires no particular supervision and can as a rule be disposed of as commercial waste that is similar to household rubbish.

European waste catalogue

07 02 08	other still bottoms and reaction residues
----------	---

Uncleaned packaging:**Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Disposal must be made according to official regulations.

14 Transport information**Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)**

ADR/RID-GGVS/E Class: 9 (M6) Miscellaneous dangerous substances and articles.

Danger code (Kemler): 90

UN-Number: 3082

Packaging group: III

Hazard label 9

Description of goods: 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)

Maritime transport IMDG/GGVSea:

IMDG/GGVSea Class: 9

UN Number: 3082

Label 9

Packaging group: III

EMS Number: F-A,S-F

Marine pollutant: Yes (P)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)

(Contd. on page 7)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK Inject Komp.A

(Contd. of page 6)

Air transport ICAO-TI and IATA-DGR:

ICAO/IATA Class: 9
UN/ID Number: 3082
Label: 9
Packaging group: III
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)

15 Regulatory information**Labelling according to EU guidelines:**

Observe the general safety regulations when handling chemicals.
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:

Xi Irritant
N Dangerous for the environment

Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Bisphenole-F-Epichlorhydrine-Resin $MG \leq 700$
oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Risk phrases:

36/38 Irritating to eyes and skin.
43 May cause sensitisation by skin contact.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

2 Keep out of the reach of children.
24/25 Avoid contact with skin and eyes.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
28 After contact with skin, wash immediately with plenty of water.
36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

Special labelling of certain preparations:

Contains epoxy constituents. See information supplied by the manufacturer.

16 Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant R-phrases

36/38 Irritating to eyes and skin.
43 May cause sensitisation by skin contact.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Department issuing MSDS: Product safety department

Contact: Mr Gilles Weber, Tel.: ++33(0)3 89 20 10 93

* Data compared to the previous version altered.

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

1 Identification of the substance/preparation and of the company/undertaking**Product details**Trade name **Eurolan FK Inject Komp.B**

Safety data sheet no.: 49PD10578-b/7

Application of the substance / the preparation Hardening agent/ Curing agent

Manufacturer/Supplier:

maxit France s.a.s
 4 rue de Mulhouse
 Boîte Postale 27
 F-68180 Horbourg-Wihr
 Tel.: ++33(0)3 89 20 10 80
 FAX: ++33(0)3 89 20 10 92

Information in case of emergency:

maxit France s.a.s
 Tel.: ++33(0)3 89 20 10 80

2 Composition/information on ingredients**Chemical characterization****Description:** Reaction resin curer based on amines and polyamines.**Dangerous components:**

2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine  C,  Xn; R 21/22-34-43-52/53	25 - 50%
25620-58-0	Trimethylhexan-1,6-diamin  C,  Xn; R 22-34-43-52/53	25 - 50%
100-51-6	Benzyl alcohol  Xn; R 20/22	10 - 20%
69-72-7	Salicylic acid  Xn,  Xi; R 22-41	5 - 10%

Additional information For the wording of the listed risk phrases refer to section 16.**3 Hazards identification****Hazard description:**

C Corrosive

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 21/22 Harmful in contact with skin and if swallowed.

R 34 Causes burns.

R 43 May cause sensitisation by skin contact.

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 2)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK Inject Komp.B

(Contd. of page 1)

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First aid measures**General information**

Immediately remove any clothing soiled by the product.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation Supply fresh air and to be sure call for a doctor.

After skin contact

Treat affected skin with cotton wool or cellulose. Then wash and rinse thoroughly with water and a mild cleaning agent.

Seek medical treatment.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth and then drink plenty of water.

Seek medical treatment.

Information for doctor

Treatment If swallowed, gastric irrigation with added, activated carbon.

5 Fire fighting measures**Suitable extinguishing agents**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents Water with full jet

Special hazards caused by the substance, its products of combustion or resulting gases:

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

Ammonia (NH₃)

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures**Person-related safety precautions:**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Measures for environmental protection:

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK Inject Komp.B

(Contd. of page 2)

The product must not get into watercourses or into the soil.

Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.

7 Handling and storage

Handling

Information for safe handling:

Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection: No special measures required.

Storage

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility:

Store away from reducing agents.
Store away from oxidizing agents.
Do not store together with alkalis (caustic solutions).
Store away from foodstuffs.

Further information about storage conditions:

Protect from heat and direct sunlight.
Protect from humidity and water.

Recommended storage temperature: 5-30°C.

8 Exposure controls and personal protection

Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information:

Te applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Use a moisturising skin cream after processing the product.
Do not eat, drink, smoke or sniff while working.

Respiratory protection:

Not necessary if room is well-ventilated.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter AX.

Protection of hands:

Protective gloves.

(Contd. on page 4)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK Inject Komp.B

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles**Body protection:** Protective work clothing.**9 Physical and chemical properties:****General Information**

Form:	Fluid
Colour:	Transparent
Odour:	Amine-like

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	>205°C (>401°F) (DIN)

Flash point: > 100°C (> 212°F) (DIN ISO 2592)

Ignition temperature: ca.400°C (ca.752°F) (DIN 51794)

Self-igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Vapour pressure at 20°C (68°F): ca. 2,0 hPa (ca. 2 mm Hg) (DIN 51640)

Density at 20°C (68°F): 1,1 g/cm³ (DIN 51757)

Bulk density: Not applicable.

Solubility in / Miscibility with

Water: Insoluble

pH-value: Not applicable.

Viscosity:

dynamic: Not determined.

kinematic: Not determined.

Solvent separation test: Not determined

Additional information: None.

10 Stability and reactivity**Thermal decomposition / Conditions to be avoided:**

No decomposition if used according to specifications.

To avoid thermal decomposition do not overheat.

(Contd. on page 5)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK Inject Komp.B

(Contd. of page 4)

Dangerous reactions:

Reacts with strong oxidizing agents

Reacts with acids

Dangerous decomposition products: No dangerous decomposition products known.**11 Toxicological information****Acute toxicity:****LD/LC50 values relevant for classification:**

Components	Type	Value	Species
2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine			
Oral	LD50	1030 mg/kg (rat)	
Dermal	LD50	1840 mg/kg (rabbit)	
25620-58-0 Trimethylhexan-1,6-diamin			
Oral	LD50	910 mg/kg (rat)	
100-51-6 Benzyl alcohol			
Oral	LD50	1230 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	4178 mg/l (rat)	
69-72-7 Salicylic acid			
Oral	LD50	891 mg/kg (rat)	
Dermal	LD50	> 2000 mg/kg (rabbit)	

Primary irritant effect:**on the skin:** Caustic effect on skin and mucous membranes.**on the eye:** Strong caustic effect.**Sensitization:** Sensitization possible through skin contact.**Additional toxicological information:**

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Harmful

Corrosive

12 Ecological information:**Information about elimination (persistence and degradability):****Other information:** The product is difficultly biodegradable.**Behaviour in environmental systems:****Mobility and bioaccumulation potential:**

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine	
Bioakkumulation	0,79 log Pow (-)
100-51-6 Benzyl alcohol	
Bioakkumulation	1,1 log Pow (-)
69-72-7 Salicylic acid	
Bioakkumulation	2,21 log Pow

(Contd. on page 6)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK Inject Komp.B

(Contd. of page 5)

Ecotoxical effects:**Aquatic toxicity:****Type of test Effective concentration Method Assessment****2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

EC 10/18h	1120 mg/l (pseudomonas putida)
EC50/24h	42 mg/l (Daphnia magna (großer Wasserfloh))
EC50/72h	37 mg/l (scenedesmus subspicatus (Alge))
LC50/48h	185 mg/l (Leuciscus idus (Goldorfe))
LC50/96h	110 mg/l (Brachydanio rerio (Zebrabärbling))

25620-58-0 Trimethylhexan-1,6-diamin

EC 10/16h	72 mg/l (pseudomonas putida)
EC50/24h	31,5 mg/l (Daphnia magna (großer Wasserfloh))
EC50/72h	29,5 mg/l (scenedesmus subspicatus (Alge))
LC0/48h	150 mg/l (Leuciscus idus (Goldorfe))
LC50/48h	174 mg/l (Leuciscus idus (Goldorfe))

100-51-6 Benzyl alcohol

EC 10	400 mg/l (pseudomonas putida)
EC50/24h	400 mg/l (Daphnia magna (großer Wasserfloh))
EC50/96h	640 mg/l (scenedesmus quadricauda (Alge))
LC50/48h	645 mg/l (Leuciscus idus (Goldorfe))
LC50/96h	10 mg/l (Lepomis macrochirus (Sonnenbarsch))
	460 mg/l (Pimephales promelas (Elritze))

69-72-7 Salicylic acid

EC50/24h	180 mg/l (Daphnia magna (großer Wasserfloh))
----------	--

Behaviour in sewage processing plants:**Type of test Effective concentration Method Assessment****100-51-6 Benzyl alcohol**

EC 50 (3h)	79 mg/l (scenedesmus quadricauda (Alge))
------------	--

Other information:**100-51-6 Benzyl alcohol**

BSB (5)	1550 mg O ₂ /g (-)
---------	-------------------------------

General notes:

Do not allow product to reach ground water, water course or sewage system.

Harmful to aquatic organisms

Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations**Product:****Recommendation**

After mixing with the resin component pour a partial amount back into the curing agent barrel, stir well and pour the mass back once more. Cured epoxy resin products are waste that requires no particular supervision and can as a rule be disposed of as commercial waste that is similar to household rubbish.

(Contd. on page 7)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK Inject Komp.B

(Contd. of page 6)

European waste catalogue

07 02 08 other still bottoms and reaction residues

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Disposal must be made according to official regulations.

14 Transport information

Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)



ADR/RID-GGVS/E Class: 8 (C7) Corrosive substances.

Danger code (Kemler): 80

UN-Number: 2735

Packaging group: III

Hazard label: 8

Description of goods: 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE, TRIMETHYLHEXAMETHYLENEDIAMINES)

Maritime transport IMDG/GGVSea:



IMDG/GGVSea Class: 8

UN Number: 2735

Label: 8

Packaging group: III

EMS Number: F-A,S-B

Marine pollutant: No

Proper shipping name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE, TRIMETHYLHEXAMETHYLENEDIAMINES)

Air transport ICAO-TI and IATA-DGR:



ICAO/IATA Class: 8

UN/ID Number: 2735

Label: 8

Packaging group: III

Proper shipping name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE, TRIMETHYLHEXAMETHYLENEDIAMINES)

EU

(Contd. on page 8)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Eurolan FK Inject Komp.B

(Contd. of page 7)

15 Regulatory information**Labelling according to EU guidelines:**

Observe the general safety regulations when handling chemicals.
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:

C Corrosive

Hazard-determining components of labelling:

3-aminomethyl-3,5,5-trimethylcyclohexylamine
Trimethylhexan-1,6-diamin

Risk phrases:

21/22 Harmful in contact with skin and if swallowed.
34 Causes burns.
43 May cause sensitisation by skin contact.
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

2 Keep out of the reach of children.
23 Do not breathe fumes.
24/25 Avoid contact with skin and eyes.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
28 After contact with skin, wash immediately with plenty of water.
36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

16 Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant R-phrases

20/22 Harmful by inhalation and if swallowed.
21/22 Harmful in contact with skin and if swallowed.
22 Harmful if swallowed.
34 Causes burns.
41 Risk of serious damage to eyes.
43 May cause sensitisation by skin contact.
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Department issuing MSDS: Product safety department**Contact:** Mr Gilles Weber, Tel.: ++33(0)3 89 20 10 93*** Data compared to the previous version altered.**