

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

1 Identification of the substance/preparation and of the company/undertaking**Product details**Trade name Superflex D 1

Safety data sheet no.: 49PD10493/10

Application of the substance / the preparation Thickener pulps

Manufacturer/Supplier:

maxit France s.a.s
 4 rue de Mulhouse
 Boîte Postale 27
 F-68180 Horbourg-Wihr
 Tel.: ++33(0)3 89 20 10 80
 FAX: ++33(0)3 89 20 10 92

Information in case of emergency:

maxit France s.a.s
 Tel.: ++33(0)3 89 20 10 80

2 Composition/information on ingredients**Chemical characterization**

Description: Ready-mixed mortar with Portland cement

Dangerous components:

14808-60-7	Siliciumdioxide (Quartzsand)		> 50%
65997-15-1	cement grey	 Xi; R 38-41-43	10 - 20%

Additional information

The preparation is "low chromate" according to 2003/53/EEC up to the best-before date, so that the identification with R 43 is not applicable.

For the wording of the listed risk phrases refer to section 16.

3 Hazards identification**Hazard description:**

Xi Irritant

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 41 Risk of serious damage to eyes.

Product has a strong alkaline reaction with water; therefore protect skin and eyes from corrosive properties.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First aid measures

General information Immediately remove any clothing soiled by the product.

After inhalation Supply fresh air; consult doctor in case of complaints.

(Contd. on page 2)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Superflex D 1

(Contd. of page 1)

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing Drink plenty of water and provide fresh air. Call for a doctor immediately.

Information for doctor None

5 Fire fighting measures

Suitable extinguishing agents

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents Water with full jet

Protective equipment: Wear self-contained respiratory protective device.

6 Accidental release measures

Person-related safety precautions:

Wear protective equipment. Keep unprotected persons away.

Avoid formation of dust.

Ensure adequate ventilation.

Measures for environmental protection:

Do not allow product to reach sewage system or any water course.

Measures for cleaning/collecting:

Pick up mechanically.

Dispose of the material collected according to regulations.

Additional information: See Section 13 for disposal information.

7 Handling and storage

Handling

Information for safe handling:

Prevent formation of dust.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Store in a cool location.

Information about storage in one common storage facility:

Do not store together with acids.

Store away from foodstuffs.

Further information about storage conditions:

Protect from humidity and water.

Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls and personal protection

Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Superflex D 1

(Contd. of page 2)

Ingredients with limit values that require monitoring at the workplace:**Additional information:**

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

Personal protective equipment:**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Keep away from foodstuffs, beverages and feed.

Do not eat or drink while working.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter P2.

Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile impregnated cotton gloves.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles

Body protection: Protective work clothing.

9 Physical and chemical properties:**General Information**

Form:	Powder
Colour:	According to product specification
Odour:	Characteristic

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

Flash point: Not applicable

Flammability (solid, gaseous): Product is not flammable.

Self-igniting: Product is not selfigniting.

(Contd. on page 4)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Superflex D 1

(Contd. of page 3)

Danger of explosion:	Product does not present an explosion hazard.
Vapour pressure:	Not applicable.
Density:	Not applicable.
Bulk density at 20°C (68°F):	1080 kg/m ³
Solubility in / Miscibility with Water at 20°C (68°F):	1,5 g/l
pH-value at 20°C (68°F):	>12,0 (DIN 19261) In water
Viscosity:	
dynamic:	Not applicable.
kinematic:	Not applicable.
Solvent content:	
Organic solvents:	0,0 %
Solids content:	100,0 %
Additional information:	None.

10 Stability and reactivity**Thermal decomposition / Conditions to be avoided:**

No decomposition if used according to specifications.

Dangerous reactions:

Reacts with acids

Reacts with light alloys in the presence of moisture to form hydrogen

Dangerous decomposition products: No dangerous decomposition products known.**11 Toxicological information****Acute toxicity:****Primary irritant effect:****on the skin:** Irritant to skin and mucous membranes.**on the eye:** Strong irritant with the danger of severe eye injury.**Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information:**Information about elimination (persistence and degradability):****Other information:** The product is difficultly biodegradable.**Ecotoxicological effects:****Remark:**

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

The product contains substances which causes severe clouding in water

Remark: The product causes a significant pH change. Neutralise before introduction.

(Contd. on page 5)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Superflex D 1

(Contd. of page 4)

General notes:

Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations**Product:****Recommendation**

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish.

European waste catalogue

10 13 11	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10
10 13 14	waste concrete and concrete sludge

Uncleaned packaging:**Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Recommended cleaning agent:

Water, if necessary together with cleansing agents.
Thoroughly shake out sacks.

14 Transport information**Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)**

ADR/RID-GGVS/E Class: -

Maritime transport IMDG/GGVSea:

IMDG/GGVSea Class: -

Air transport ICAO-TI and IATA-DGR:

ICAO/IATA Class: -

Transport/Additional information: Not dangerous according to the above specifications.

15 Regulatory information**Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
Observe the general safety regulations when handling chemicals.

Code letter and hazard designation of product:

Xi Irritant

Hazard-determining components of labelling:

cement grey

Risk phrases:

41 Risk of serious damage to eyes.

(Contd. on page 6)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Superflex D 1

(Contd. of page 5)

Safety phrases:

- 2 Keep out of the reach of children.
- 22 Do not breathe dust.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 28 After contact with skin, wash immediately with plenty of water.
- 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- 46 If swallowed, seek medical advice immediately and show this container or label.

Special labelling of certain preparations:

Product has a strong alkaline reaction with water; therefore protect skin and eyes from corrosive properties.

16 Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant R-phrases

- 38 Irritating to skin.
- 41 Risk of serious damage to eyes.
- 43 May cause sensitisation by skin contact.

Department issuing MSDS: Product safety department

Contact: Mr Gilles Weber, Tel.: ++33(0)3 89 20 10 93

*** Data compared to the previous version altered.**

EU