

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

1 Identification of the substance/preparation and of the company/undertaking

Product details

Trade name **Superflex FDF**

Safety data sheet no.: 49PD10494/8

Application of the substance / the preparation

Construction chemicals

Sealing

Manufacturer/Supplier:

maxit France s.a.s

4 rue de Mulhouse

Boîte Postale 27

F-68180 Horbourg-Wihr

Tel.: ++33(0)3 89 20 10 80

FAX: ++33(0)3 89 20 10 92

Information in case of emergency:

maxit France s.a.s

Tel.: ++33(0)3 89 20 10 80

2 Composition/information on ingredients

Chemical characterization

Description: Styrene acrylate dispersion

Dangerous components:

64742-47-8	Distillates (petroleum),hydrotreated light	 Xn,  N; R 10-51/53-65-66-67	1 - 2%
------------	--	---	--------

Additional information For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

Hazard description: Not applicable.

Information concerning particular hazards for human and environment:

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First aid measures

General information Immediately remove any clothing soiled by the product.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

Generally the product does not irritate the skin.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

(Contd. on page 2)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Superflex FDF

Information for doctor None

(Contd. of page 1)

5 Fire fighting measures**Suitable extinguishing agents**

Use fire extinguishing methods suitable to surrounding conditions.

Special hazards caused by the substance, its products of combustion or resulting gases:

When water is vaporized, generation of toxic gases can not be excluded, e.g.: Carbon monoxide (CO)

Protective equipment: Use methods suitable to surrounding conditions.

6 Accidental release measures**Person-related safety precautions:**

Wear protective clothing.

Ensure adequate ventilation.

Measures for environmental protection:

The product must not get into watercourses or into the soil.

Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

Additional information: See Section 13 for disposal information.

7 Handling and storage**Handling****Information for safe handling:**

Keep away from heat and direct sunlight.

Store in cool, dry place in tightly closed receptacles.

Information about fire - and explosion protection: No special measures required.

Storage**Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Protect from frost.

Store in cool, dry conditions in well sealed receptacles.

Recommended storage temperature: 5-30°C.

8 Exposure controls and personal protection

Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information:

Te applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Superflex FDF

(Contd. of page 2)

Personal protective equipment:**General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Immediately remove all soiled and contaminated clothing.

Respiratory protection: Not required.**Protection of hands:**

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Rubber gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety glasses.**Body protection:** Protective work clothing.**9 Physical and chemical properties:****General Information**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

Change in condition**Boiling point/Boiling range:** 100°C (212°F) (DIN)**Flash point:** Not applicable**Self-igniting:** Product is not selfigniting.**Danger of explosion:** Product does not present an explosion hazard.**Vapour pressure at 20°C (68°F):** 23 hPa (17 mm Hg) (DIN 51640)**Density at 20°C (68°F):** 1,6 g/cm³ (DIN 51757)**Bulk density:** Not applicable.**Solubility in / Miscibility with****Water:** Fully miscible**pH-value at 20°C (68°F):** 8,0-9,0 (DIN 19261)**Viscosity:****dynamic:** Not determined.**kinematic:** Not determined.**Solvent separation test:** Not determined**Solvent content:****Organic solvents:** < 1,5 %

(Contd. on page 4)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Superflex FDF

(Contd. of page 3)

Additional information: None.

10 Stability and reactivity**Thermal decomposition / Conditions to be avoided:**

No decomposition if used according to specifications.

Materials to be avoided: Product coagulation occurs when acid substances are added**Dangerous reactions:** No dangerous reactions known**Dangerous decomposition products:** No dangerous decomposition products known.**11 Toxicological information****Acute toxicity:****LD/LC50 values relevant for classification:**

Components	Type	Value	Species
63449-39-8 Paraffin waxes and Hydrocarbon waxes, chloro			
Oral	LD50	>2000 mg/kg (rat)	
64742-47-8 Distillates (petroleum),hydrotreated light			
Oral	LD50	> 2000 mg/kg (rat)	
Dermal	LD50	> 2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	> 5 mg/l (rat)	

Primary irritant effect:**on the skin:** No irritant effect.**on the eye:** No irritating effect.**Sensitization:** No sensitizing effects known.**Additional toxicological information:**

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

12 Ecological information:**Information about elimination (persistence and degradability):****Other information:** The product is difficultly biodegradable.**Ecotoxicological effects:****Aquatic toxicity:**

Type of test	Effective concentration	Method	Assessment
63449-39-8 Paraffin waxes and Hydrocarbon waxes, chloro			
EC50/24h	130 mg/l	(fish)	
64742-47-8 Distillates (petroleum),hydrotreated light			
IC50/72h	< 10 mg/l	(Alge)	
LC50/96h	< 10 mg/l	(fish)	

Remark: The product contains substances which causes severe clouding in water**General notes:**

Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 5)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Superflex FDF

Danger to drinking water if even small quantities leak into the ground.

(Contd. of page 4)

13 Disposal considerations**Product:****Recommendation**

After prior treatment product has to be landfilled adhering to the regulations pertaining to the disposal of particularly hazardous waste.

Waste disposal key:

The classification in a waste code according to the European waste catalogue (EWC) is to be made in accordance with the regional responsible for waste disposal

Uncleaned packaging:**Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Recommended cleaning agent: Water, if necessary together with cleansing agents.

14 Transport information**Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)**

ADR/RID-GGVS/E Class: -

Maritime transport IMDG/GGVSea:

IMDG/GGVSea Class: -

Air transport ICAO-TI and IATA-DGR:

ICAO/IATA Class: -

Transport/Additional information: Not dangerous according to the above specifications.

15 Regulatory information**Labelling according to EU guidelines:**

The product is not subject to classification according to the calculation methods of the "General Classification Guideline for Preparations of the EU" as issued in the latest valid version. Observe the general safety regulations when handling chemicals.

Special labelling of certain preparations:

Safety data sheet available for professional user on request.

16 Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant R-phrases

10 Flammable.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 6)

Material Safety Data Sheet
According to 91/155 EEC

Printing date 04.04.2007

Reviewed on 21.03.2007

Trade name Superflex FDF

67 Vapours may cause drowsiness and dizziness.

(Contd. of page 5)

Department issuing MSDS: Product safety department**Contact:** Mr Gilles Weber, Tel.: ++33(0)3 89 20 10 93*** Data compared to the previous version altered.**

EU